

Y251D

PREMIUM GRADE DOUBLE-COATED UPVC FILM TAPE

DESCRIPTION

2.0 mil UPVC film coated on both sides with pressure-sensitive acrylic adhesive that provides exceptional shear and peel adhesion and good initial tack allowing immediate/permanent bond to a variety of surfaces such as wood, glass, cement and plastics (including irregular and porous surfaces). Solvent, chemical, UV and heat resistant. Features an easy release 3 mil glassine paper liner 60# (yellow).

Product is not repulpable.

PRODUCT APPLICATION

Mounting decorative trims such as PVC profile for the furniture industry, fastening of nameplates, trophy, luggage tags, wooden trim, signs, etc. Can also be used for splicing, and many applications that require the joining of two surfaces.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 08/16

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	2.0 mil (50μ) UPVC film
Adhesive	Solvent Acrylic
Adhesion to Steel (oz/in of width) PSTC-101	91.5 (2.8 kg/25mm)
Total Thickness (mils) PSTC-133	8.0 (0.20mm) with liner 5.0 (0.13mm) w /o liner
Shear Adhesion to Steel (hours) 1" x 1" x 1 kg @ 176°F (80°C) PSTC-107	> 72
Service Temperature	-4°F to +194°F (-20°C to +90°C)
Color	Clear

