

# TM27

## SPECIALTY TRIMFAST MASKING TAPE

### DESCRIPTION

Stain resistant, temperature resistant, paper masking tape combined with strong PET (polyester) film as insertion lip for painting around window lacings. Lifts moldings away to permit sanding, preparation for easy cornering/curved surfaces. Re-positionable rubber based pressure-sensitive adhesive provides secure hold to and clean removal for bonded / fixed screen rubbers and flush mount / insert moldings around windshield and other automotive glass.

### PRODUCT APPLICATION

For use on corner and straight moldings around windshield and other automotive glass.

## INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Backing</b>	Crepe Paper/PET Film
<b>Adhesive</b>	Rubber/Resin
<b>Total Thickness</b> (mils)	7.6 (0.19mm)
<b>Peel Adhesion</b> (oz/in of width)	30 (8.2 N/25mm)
<b>Temperature Resistance</b>	107°C (225°F)
<b>UV Resistance</b>	Limited
<b>Weather Resistance</b>	Limited
<b>Color</b>	Natural



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 01/19

