

815

150# TENSILIZED MEDIUM GRADE MOPP

DESCRIPTION

A medium duty mono-oriented polypropylene (MOPP) strapping tape with a synthetic rubber/resin adhesive. Waterproof, chemical and stain resistant. Provides safe, secure holding power and protection with clean removal from a variety of surfaces. Product testing is recommended.

PRODUCT APPLICATION

Designed for demanding applications, including metal office furniture, small appliances, parts, etc. Product can also be used for general to heavy-duty strapping, tabbing, bundling, and palletizing.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 11/13

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	MOPP Film
Adhesive	Synthetic Rubber/Resin
Adhesion to Steel (oz/in of width) PSTC-101	82 (22.4 N/25mm)
Tensile Strength (lbs/in of width) PSTC-131	150 (667 N/25mm)
Elongation (% at break) PSTC-133	34
Total Thickness (mils)	4.6 (0.117mm)
Quick Stick (oz/in of width) To Steel: To Kraft:	48 (13 N/25mm) 8 (2.2 N/25mm)
Operating Temperature Range	+40°F ~ +150°F (+4°C ~ +65°C)
Color	Ivory

