



INDUSTRIAL GRADE PAPER MASKING TAPE

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

A green crepe paper masking tape coated with a stain resistant pressure-sensitive adhesive. Capable of withstanding oven temperatures up to 225°F (107°C) for one hour. Compatible with both water and solvent-based paints.

PRODUCT APPLICATION

Automotive, truck, bus, RV and marine paint masking.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Crepe Paper
Adhesive	Natural/Synthetic Rubber
Adhesion to Steel (oz/in of width) PSTC-101	35 (9.8 N/25mm)
Tensile Strength (lbs/in of width) PSTC-131	22 (96.3 N/25mm)
Elongation (% at break) PSTC-131	9
Total Thickness (mils) PSTC-133	5.8 (0.147mm)
Quick Stick to Steel (oz/in of width) PSTC-105	15 (4.1 N/25mm)
Color	Light Green



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
 Customer Service: 800.IPG.8273 | 800.474.8273
 Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 10/19

