

## POLYETHYLENE MASKING TAPE FOR STUCCO APPLICATION



**U.V. RESISTANT**

**HIGH HOLDING POWER**

### Please note:

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness.

The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded.

No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

### DESCRIPTION

This tape is made of a red polyethylene film and coated with a natural rubber adhesive. This tape is designed for masking and protecting surfaces during stucco application. Recommended as well as general protective tape, repair tape and identification tape. Removes clean with up to 30 days exposure to sunlight.

### MAIN FEATURES

- Polyethylene film conforms very well to all type of surfaces.
- The strong adhesive will hold on rough surfaces.
- Moisture resistant.
- Clean removal with up to 30 days exposure to sunlight.

### APPLICATIONS

- Protective masking for non-painted surfaces such as wood, glass, steel, vinyl and aluminum.
- Indoor and outdoor application.
- Splicing and holding polyethylene sheeting.
- Patching and repairing a variety of surfaces.

### TECHNICAL DATA

Colour .....	Red
Backing .....	Polyethylene film
Adhesive.....	Natural rubber
Thickness.....	7 mil
Adhesion to steel .....	50 oz/in
Tensile strength .....	23 lb/in
Elongation .....	99%
Temperature Resistance .....	176°F (80°C) for 30 minutes
Application Temperature .....	41°F (5°C) to 122°F (50°C)
VOC (Volatile Organic Compound) content .....	0%

### EXAMPLE OF APPLICATION

