

RG22

253# PET SPECIALTY FILAMENT TAPE

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

A clear, glass reinforced, polyester backed strapping tape with pressure-sensitive natural rubber/resin adhesive. High tensile strength, high adhesion and medium impact strength. Stain resistant and will not impart an odor or taste.

PRODUCT APPLICATION

Used in the appliance and furniture industries for securing components where direct contact with and subsequent removal from the surface of appliances is a factor. Product further provides safe, secure holding power to a variety of surfaces for packaging, bundling and palletizing applications.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	1.42 mil (0.036 mm) Polyester Film
Adhesive	Natural Rubber / Resin
Reinforcement	Fiberglass
Adhesion to Steel (oz/in of width) (at 90° peel angle) ASTM D3330	46 (12.6 N/25mm)
Tensile Strength (lbs/in of width) ASTM D3759	253 (1108 N/25mm)
Elongation (% at break) ASTM D3759	4
Total Thickness (mils) ASTM D3652	7.0 (0.178 mm)
Quick Stick (oz/in of width) To Kraft To Steel	6 (1.6 N/25mm) 34 (9.3 N/25mm)
Color	Natural



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 11/13

