

RG46

7.0 MIL HIGH TEMPERATURE GLASS CLOTH TAPE

DESCRIPTION

Woven fiberglass pressure-sensitive tape. Can withstand exposure to temperatures up to 400°F (204°C) for many hours, 300°F (148°C) for several weeks, and 250°F (121°C) permanently. The thermosetting properties of the adhesive provide resistance to strong solvents (e.g. xylene, toluene). The cure rate of the adhesive is time / temperature dependant.

PRODUCT APPLICATIONS

Tensile strength, dimensional stability, and consistent thickness, combined with high holding properties makes RG46 an excellent choice for splicing, especially materials having rough surfaces and/or low internal strength (e.g. textiles, roofing materials).

GOVERNMENT CONFORMANCE

MIL-T-4053B



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 11/13

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	5 mil (0.127mm) Glass Cloth
Adhesive	Thermosetting Rubber
Tensile Strength (lbs/in of width)	175 (766 N/25mm)
Adhesion to Steel (oz/in of width)	50 (13.7 N/25mm)
Elongation (% at break)	3
Total Thickness (mils)	7.0 mil (0.178mm)
Color	White, Black

